



Image shown may not reflect actual package.

PRIME 800 ekW 1000 kVA 50 Hz 1500 rpm 400 Volts

Caterpillar® is leading the power generation marketplace with Power Solutions engineered to deliver unmatched flexibility, expandability, reliability, and cost-effectiveness.

FEATURES

FUEL/EMISSIONS STRATEGY

- Low emissions

SINGLE-SOURCE SUPPLIER

- Complete systems designed and built at Caterpillar ISO certified facilities.
- Fully prototype tested with certified torsional vibration analysis available

WORLDWIDE PRODUCT SUPPORT

- Worldwide parts availability through the Caterpillar dealer network
- With over 1844 dealer branch stores operating in 166 countries, you're never far from the Caterpillar part you need
- 99.7% of parts orders filled within 24 hours. The best product support record in the industry
- Caterpillar dealer service technicians are trained to service every aspect of your electric power generation system
- Preventive maintenance agreements
- The Cat Scheduled Oil Sampling (S•O•SSM) program cost effectively detects internal engine component condition, even the presence of unwanted fluids and combustion by-products



CAT® 3508B TA DIESEL ENGINE

- Reliable, rugged, durable design
- Field-proven in thousands of applications worldwide
- Four-stroke-cycle diesel engine combines consistent performance and excellent fuel economy with minimum weight
- UL 2200 Listed packages are available. Certain restrictions may apply. Consult with you Caterpillar dealer



CAT SR4B GENERATOR

- Designed to match performance and output characteristics of Caterpillar diesel engines
- Optimum winding pitch for minimum total harmonic distortion and maximum efficiency
- Single point access to accessory connections
- UL 1446 recognized Class H insulation system



CAT CONTROL PANELS

- Three levels of controls, designed to meet individual customer needs:
 - EMCP II provides digital monitoring, metering, and protection
 - EMCP II+ provides EMCP II features along with full-featured power metering and protective relaying (optional)
 - Switchgear conversions provides easy interface for remote switchgear
- UL 508A Listed

FACTORY INSTALLED STANDARD & OPTIONAL EQUIPMENT

System	Standard	Optional
Air Inlet	<ul style="list-style-type: none"> • Single element canister type air cleaner • Service indicator 	<ul style="list-style-type: none"> • Dual element & heavy duty air cleaners • Air inlet adapters & shutoff
Cooling	<ul style="list-style-type: none"> • Radiator with guard (43°C) • Coolant drain line with valve • Fan and belt guards • Caterpillar Extended Life Coolant • Low coolant level & high temperature alarm or shut-down 	<ul style="list-style-type: none"> • Radiator with 50°C ambient capability • Radiator removal • Heat exchanger and expansion tank • Radiator duct flange • Coolant level switch gauge • Jacket water heater
Exhaust	<ul style="list-style-type: none"> • Stainless steel exhaust flex and ANSI outlet flange 	<ul style="list-style-type: none"> • Mufflers (10, 25, & 35 dba) • Elbow kit and through-wall installation kit
Fuel	<ul style="list-style-type: none"> • Primary & secondary fuel filters • Fuel priming pump • Flexible fuel lines 	<ul style="list-style-type: none"> • Fuel cooler • Water separator
Generators	<ul style="list-style-type: none"> • Permanent magnet excited • Class H insulation • Class F temperature (105°C prime/130°C standby) • Reactive droop • Digital Voltage Regulator, 3-phase sensing • Bus bar connections • Winding temperature detectors • Anti-condensation space heaters 	<ul style="list-style-type: none"> • Digital Voltage Regulator with KVAR/PF control • Bearing temperature detectors • Oversize & premium generators • Cable access box • Neutral grounding connection • Circuit breakers, IEC compliant, 3 & 4 pole with shunt trip
Governing	<ul style="list-style-type: none"> • ADEM II 	<ul style="list-style-type: none"> • Low emissions conversion
Control Panels	<ul style="list-style-type: none"> • EMCP II 	<ul style="list-style-type: none"> • EMCP II+ • EMCP II+ with Auto-Paralleling • Switchgear conversion • Customer Communication Module • Local alarm & remote annunciator modules
Lube	<ul style="list-style-type: none"> • Lubricating oil and filter • Oil drain line with valves • Fumes disposal 	<ul style="list-style-type: none"> • Sump pump (manual) • Sump & prelube pump (manual or electric) • Oil level regulator
Mounting	<ul style="list-style-type: none"> • 330 mm (13 in) structural steel rails • Spring-type, anti-vibration mounts (shipped loose) 	
Starting/Charging	<ul style="list-style-type: none"> • 24 volt starting motor(s) • 45 amp charging alternator • Batteries with rack and cables • Battery disconnect switch 	<ul style="list-style-type: none"> • Battery chargers (5 or 10 Amp) • Oversize batteries • Ether starting aids • Heavy duty starting motors • Barring device (manual)
General		<ul style="list-style-type: none"> • Crankcase explosion relief valves • Automatic transfer switches (ATS) • EU Certificate of Conformance

TECHNICAL DATA

Open Generator Set - — 1500 rpm/50 Hz/400 Volts	PRIME DM2983	
Package Performance Power rating @ 0.8 pf Power rating	1000 kVA 800 ekW	
Low Emissions Coolant to aftercooler temp max	90 Deg C	194 Deg F
Fuel Consumption 100% load with fan 75% load with fan 50% load with fan	218.3 L/hr 164.6 L/hr 114.6 L/hr	57.7 Gal/hr 43.5 Gal/hr 30.3 Gal/hr
Cooling System* Ambient air temperature Air flow restriction (system) Air flow (max @ rated speed for radiator arrangement) Engine coolant capacity Radiator coolant capacity Engine coolant capacity with radiator	43 Deg C .18 kPa 738 m ³ /min 102.7 L 450.0 L 552.7 L	109 Deg F 0.72 in. water 26,062 cfm 27.1 Gal 118.9 Gal 146.0 Gal
Exhaust System Combustion air inlet flow rate Exhaust stack gas temperature Exhaust gas flow rate Exhaust flange size (internal diameter) Exhaust system backpressure (maximum allowable)	69.8 m ³ /min 446.8 Deg C 175.6 m ³ /min 203.2 mm 6.7 kPa	2,465.0 cfm 836 Deg F 6,201.3 cfm 8.0 in 26.9 in. water
Heat Rejection Heat rejection to coolant (total) Heat rejection to exhaust (total) Heat rejection to atmosphere from engine Heat rejection to atmosphere from generator	410 kW 771 kW 103 kW 42.13 kW	23,317 Btu/min 43,847 Btu/min 5,858 Btu/min 2,395.93 Btu/min
Alternator** Motor starting capability @ 30% voltage dip Frame Temperature Rise	1932 skVA 693 105 Deg C	
Emissions (Nominal)*** NOx mg/nm3 CO mg/nm3 HC mg/nm3 PM mg/nm3	2970.8 mg/nm3 145.4 mg/nm3 70.7 mg/nm3 35.6 mg/nm3	

*Ambient capability at 200 m (660 ft) above sea level. For ambient capability at other altitudes, consult your Caterpillar dealer.

**Generator temperature rise is based on a 40 degree C ambient per NEMA MG1-32.

***Emissions data measurements are consistent with those described in EPA CFR 40 Part 89, Subpart D & E and ISO8178-1 for measuring HC, CO, PM, NOx. This engine's exhaust emissions are in compliance with the US EPA and California nonroad regulations as identified above. Data shown is based on steady state operating conditions of 77° F, 28.42 in HG and number 2 diesel fuel with 35° API and LHV of 18,390 btu/lb. The nominal emissions data shown is subject to instrumentation, measurement, facility and engine to engine variations.

PRIME 800 e k W 1000 k V A
50 H z 1500 r p m 400 V o l t s



RATING DEFINITIONS AND CONDITIONS

Meets or Exceeds International Specifications: · ABGSM TM3, AS1359, AS2789, BS4999, BS5000, BS5514, DIN6271, DIN6280, EGSA101P, IEC34/1, ISO3046/1, ISO8528, JEM1359, NEMA MG 1-22, VDE0530, 89/392/EEC, 89/336/EEC

Prime - Output available with varying load for an unlimited time. Prime power in accordance with ISO8528. 10% overload power in accordance with ISO3046/1, AS2789, DIN6271, and BS5514 available on request. Prime power ambients shown indicate ambient at 100 percent load which results in a coolant top tank temperature just below the alarm temperature.

Ratings are based on SAE J1995 standard conditions. These ratings also apply at ISO3046/1, DIN6271, and BS5514 standard conditions.

Fuel Rates are based on fuel oil of 35° API (16° C or 60° F) gravity having an LHV of 42 780 kJ/kg (18,390 Btu/lb) when used at 29° C (85° F) and weighing 838.9 g/liter (7.001 lbs/U.S. gal.).

Additional Ratings may be available for specific customer requirements. Consult your Caterpillar representative for details.

Package Dimensions		
Length	5292.2 mm	208.35 in
Width	1844.0 mm	72.6 in
Height	2230.0 mm	87.8 in
Weight	10 477 kg	23,098 lb

Note: Do not use for installation design.
See general dimension drawings
for detail (Drawing #1533623).



TMI Reference No.: DM2983

PL Reference No.: 508DE49

European Sourced

LEHE2454 9 April 2002

42130

www.CAT-ElectricPower.com

©2002 Caterpillar
All rights reserved.

Materials and specifications are subject to change without notice.
The International System of Units (SI) is used in this publication.